



Specifications Ledvance LED Floodlight Endura Black 27W 3000lm 100D - 840 Cool White | IP55 - Motion and Light Sensor - Symmetrical

[View Product](#)

General Information

|                          |                               |
|--------------------------|-------------------------------|
| SKU                      | 236754                        |
| EAN                      | 4058075228849                 |
| Brand                    | Ledvance                      |
| Manufacturer Name        | E PRO FLOOD S 27W 840 IP55 DG |
| Any Lamp all-in warranty | 5 Years                       |
| Average Lifetime (h)     | 30000                         |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 27              |
| Replaces (Watt)             | 50              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 3000            |
| Luminous Efficacy (lm/W)    | 111             |

|                       |                |
|-----------------------|----------------|
| Beam Angle (degree)   | 100            |
| Power factor          | >0.90          |
| Product Type Category | LED Floodlight |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Surface                     |
| Including bulb         | Yes                         |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |
| Optical Cover          | Polycarbonate (PC)          |
| Light Distribution     | Symmetrical                 |
| IP-rating              | IP55                        |
| Impact Protection (IK) | IK05 - 0.70 joule           |
| Operating Temperature  | -20 to +40                  |
| Colour of the Fixture  | Dark Grey                   |
| Housing                | PC (Polycarbonate)          |
| Colour of material     | Grey                        |
| Series                 | Endura                      |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 201 |
| Width (mm)  | 56  |
| Height (mm) | 225 |

## Why Any-lamp?

## Sensor Information

|                                                                                                    |                                                                                            |                                                                                                                   |
|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
|  Type of sensor | Order from the <b>largest lighting specialist in Europe</b><br>Light Sensor, Motion Sensor |  <b>Customised quotation</b> |
| Sensor Reach (m)                                                                                   | 1,5 m - 12 m                                                                               |                                                                                                                   |
| Sensor Time Setting                                                                                | 2 sec - 15 min                                                                             |                                                                                                                   |